



Typical Inspection Data:

Density @ 20 °C	0.858 g/cm ³
Viscosity @ 100 °C	9.3 cSt
Viscosity @ 40 °C	54 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39 °C

Performance Profile:

Recommended by Comma for certain Citroën, Peugeot, Renault, Nissan & Mazda applications and generally where a 75W80, API GL4 oil is specified. Suitable for use where the following specifications are called for:

PSA B71 2330	API GL-4
Esso EZL 848	API GL-3 (75W-80)
Renault Tranself TRJ 75W80	
Renault Tranself TRT 75W80	

EP75W80 Plus Mineral

Product Features:

- Enhanced mineral gear oil suitable for certain Rover, Peugeot, Citroën and Renault manual gearboxes.
- Good low temperature performance.
- Robust corrosion protection.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

30-11-2017