



## Typical Inspection Data:

Density @ 20°C	0.847 g/cm <sup>3</sup>
Viscosity @ 100°C	7.5 cSt
Viscosity @ 40°C	35 cSt
Phosphorus	0.03%
Colour	Red
Pour Point	-45°C

## Performance Profile:

Recommended by Comma for certain Aisin-Warner automatic transmissions in Ford, Saab, Toyota, Volkswagen & Volvo vehicles. Suitable for use where the following specifications are called for:

ATF, JWS 3309	ATF, Toyota Type T-IV
ATF, VW G 055 025	Ford WSS-M2C924-A
Volvo 1161540	

## ASW Semi Synthetic

### Product Features:

- Specific to Aisin-Warner automatic transmissions.
- Suitable for a number of applications including Saab & Volvo.
- To ensure correct oil selection check Comma's latest Application guide in store or online at [CommaOil.com](http://CommaOil.com)

### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

### Pack Size Availability:



15-06-2016