

Technical Data Sheet



Typical Inspection Data:

Density @ 20 °C	0.847 g/cm ³
Viscosity @ 100 °C	15.2 cSt
Viscosity @ 40 °C	90 cSt
Phosphorus	0.02%
Colour	Light Straw
Pour Point	-36 °C

Performance Profile:

Recommended by Comma for certain applications where a 75W-90, 80W-90 or 85W-90 API GL-4 oil is specified. Suitable for use where the following specifications are called for:

API GL-4	Ford M2C175-A
API GL-3 (75W-85 & 75W-90)	

SX75W-90 GL-4

Semi Synthetic

Product Features:

- Suitable for modern five and six speed gear boxes.
- Recommended by Comma for applications requiring a 75W-90, 80W-90 or 85W-90 API GL-4 oil.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

30-11-2017