



## Typical Inspection Data:

<b>Colour</b>	Amber
<b>Texture</b>	Smooth
<b>NLGI</b>	2 (Medium)
<b>Worked Penetration @ 25 °C</b>	280 mm <sup>10</sup> <sup>-1</sup>
<b>Drop Point</b>	200°C
<b>Operating Temperature Range</b>	-10 °C to +120 °C
<b>Oil Separation (168 hrs @ 40 °C)</b>	<7%
<b>Copper Corrosion (24 hrs @ 100 °C)</b>	1a
<b>Water Washout @ 38 °C</b>	<7%

## Multipurpose Lithium Grease

### Product Features:

- Lithium-based grease with good temperature tolerance. Suitable for hubs, universal joints, chassis and general greasing.
- Long life for use in well-sealed bearings.
- Oxidation inhibited – Ensures long life in storage.
- Good water resistance – Provides satisfactory lubrication in the presence of water and is not washed out of bearings.
- Good corrosion protection – Rust inhibited to protect bearing surfaces.

### Handling:

- Never over pack the bearing.
- It is sound lubrication practice to remove the old grease before a new grease is introduced.
- If used grease cannot be removed, Comma Multipurpose grease is generally compatible with other lithium greases.
- When mixed with other grease types, this grease should be satisfactory below an operating temperature of 80 °C.
- Avoid extremes of temperature.
- Store under cover.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.

28-02-2017